

АВТОКРАН



ИВАНОВЕЦ

KC-55735-6

30,3 (39,0) m

KAMAZ

35 t



- Truck crane KC-55735-6 is designed for construction-assembly works and handling operations of regular loads.
- Chassis: KAMAZ-6540 of emission standard Euro 2 / Euro 3 / Euro 4 / Euro 5
- Maximum lifting capacity: 35 t
- Crane mechanisms drive: hydraulic with the possibility of combining of work operations.
- Boom: three sections telescopic. Boom telescoping is performed with a hydraulic cylinder and a block and tackle system. In order to increase length of the boom a 9.0 m jib to be equipped.
- Lifting limitation and fixing of the crane operation parameters: using a microprocessor lifting limiter with a digital information display and a built-in data recorder.

Technical Specifications

KC-55735-6

Chassis	KAMAZ-6540	Maximum speed of lifting (lowering) the hook, m/min	38,0
Axle configuration	8 x 4	Precision load-lowering speed, m/min	0,2
Max. lifting capacity, tn	35	Slewing speed, min-1	0,3 - 1,0
Load moment, tm	105	Travelling speed, km/h	60,0
Support contour, m	7,4 x 6,5	Dimensions, mm	
Boom length, m	10,1 - 30,3	length	11 800
Jib length, m	9,0	width	2 550
Maximum load-lifting height, m		height	4 000
with main boom	30,3	Gross weight with jib, t	26,63 (27.13)
with jib	39,0	Axle load, t	
Working radius, m		weight on front axle	11.53 (12.03)
with main boom	3,0 - 28,0	weight on rear axle	15.10 (15.10)
with jib	10,0 - 34,0		
Working speed at 10 lines reeving, m/min	0,2 - 5,1		

Load Chart

360° rotation

